



24W EMERGENCY BATTERY FOR HBX1 HIGH BAYS (120-277V MODELS)

Catalog #	
Project	
Date	
Prepared by	
Model #	HB-24EBX1

OVERVIEW

The HB-24EBX1 Emergency Battery Driver works with all 120-277V HBX1 models. When there is a power outage, this emergency battery driver will provide the HBX1 with power to the LED driver for 90 minutes.



PRODUCT HIGHLIGHTS

- Fits all 120-277V HBX1-Series High Bays
- <5 second response time
- 90 minute operating time
- Ni-cd 14.4V 57.6WH Battery
- 5 year warranty

ELECTRICAL SPECIFICATIONS		APPROVALS & LISTINGS	
Power (W)	24.5W	UL/ETL Listed	cULus
Input Voltage	100-277V	EMERGENCY BATTERY DETAILS	
Output Voltage (VDC)	Dip switch selectable: 18-24VDC/24-36VC/ 36-42VDC/42-48VDC	Charging Time	24 hours
CONSTRUCTION		Battery Type	Nickel-Cadmium 14.4V, 57.6WH
Housing Material	Galvanized steel enclosure	Standby Power	<6W
Housing Color	Black	Response Time	<5 seconds.
Dimensions (inch/mm)	325.3mm x 116.6mm x 207.5mm 12.81" x 4.59" x 8.17"	Emergency Time	90 minutes
Weight (kg/lbs)	3.6kg / 7.94 lbs	Operating Temperature/Humidity	-0°~ +50°/10%RH-80%RH
Installation Method	Screw and fasten (screws included)		

PRODUCT DIMENSIONS

