



IES Distribution Type III or Type IV

High Efficacy, Up to 136 lm/W

100-277V & 277-480V

4000K CCT



FL4-Series Area Lights



The FL4-Series Area Light is our specification grade exterior lighting collection designed for area and site lighting. Finished in black, its sleek design and larger housing size provides an attractive look, providing a modern feel that's perfect for downtown areas, hospital grounds, college campuses, shopping malls, and business complexes.

Offered in IES Distribution Types III or IV and with optional integrated controls, they are a high efficacy solution that allows you to achieve any area lighting requirement.

Key Features & Benefits

- Choice of IES Distribution Type III "Bat-Wing" or Type IV "Forward-Throw" beam patterns
- Designed to be used with mounting arm attachment for area lighting applications (sold separately)
- Operates in -40°F/-40°C degree outdoor weather
- 1-10V dimming for maximum control and energy savings
- IP65 and Wet Location rated
- Black contemporary finish to complement all outdoor environments
- Available with integrated motion sensor (120-277V only, sold separately) and Photocell (120V only, sold separately)

*Fixture does not include a mounting arm. Mounting arm must be added upon ordering.

WHY CHOOSE THIS FIXTURE?

MOUNTING ARM-READY

Combine the fixture with a mounting arm attachment to 90° /surface mount for area lighting applications

LARGER FORM FACTOR

A sleek and modern look with a housing designed slightly larger to pair well aesthetically with the poles they are installed on

AVAILABLE INTEGRATED MOTION SENSOR

Blends in with the sleek design of the housing (available for 100-277V models)

IES DISTRIBUTION TYPE OPTIONS

Choose between two IES Distribution Types:

- Type III "Bat-Wing"
- Type IV "Forward Throw"

OPTIONAL GLARE SHIELD

Easily add a glare shield and control area lighting to eliminate light trespass

Available Models

MODEL#	VOLTAGE	WATTAGE	LUMEN	CRI	BEAM ANGLE	CCT	DIMMABLE
FL4-804T3-1	100-277VAC	80W	11145	82	IES Type III	4000K	1-10V
FL4-804T3-2	277-480VAC	80W	10833	82	IES Type III		
FL4-804T4-1	100-277VAC	80W	11113	82	IES Type IV		
FL4-804T4-2	277-480VAC	80W	11113	82	IES Type IV		
FL4-1004T3-1	100-277VAC	100W	14126	80	IES Type III		
FL4-1004T3-2	277-480VAC	100W	14126	80	IES Type III		
FL4-1004T4-1	100-277VAC	100W	13944	80	IES Type IV		
FL4-1004T4-2	277-480VAC	100W	13944	80	IES Type IV		
FL4-1504T3-1	100-277VAC	150W	20741	80	IES Type III		
FL4-1504T3-2	277-480VAC	150W	20062	80	IES Type III		
FL4-1504T4-1	100-277VAC	150W	20022	81	IES Type IV		
FL4-1504T4-2	277-480VAC	150W	20022	81	IES Type IV		
FL4-2004T3-1	100-277VAC	200W	27941	80	IES Type III		
FL4-2004T3-2	277-480VAC	200W	27941	80	IES Type III		

Available Models							
MODEL#	VOLTAGE	WATTAGE	LUMEN	CRI	BEAM ANGLE	CCT	DIMMABLE
FL4-2004T4-1	100-277VAC	200W	28205	80	IES Type IV	4000K	1-10V
FL4-2004T4-2	277-480VAC	200W	28205	80	IES Type IV		
FL4-2404T3-1	100-277VAC	240W	33004	80	IES Type III		
FL4-2404T3-2	277-480VAC	240W	33004	80	IES Type III		
FL4-2404T4-1	100-277VAC	240W	32871	80	IES Type IV		
FL4-2404T4-2	277-480VAC	240W	32871	80	IES Type IV		
FL4-3104T3-1	100-277VAC	300W	40382	80	IES Type III		
FL4-3104T3-2	277-480VAC	300W	40265	80	IES Type III		
FL4-3104T4-1	100-277VAC	300W	40421	80	IES Type IV		
FL4-3104T4-2	277-480VAC	300W	40326	80	IES Type IV		
FL4-4504T3-1	100-277VAC	450W	57000	80	IES Type III		
FL4-4504T3-2	277-480VAC	450W	57375	80	IES Type III		
FL4-4504T4-1	100-277VAC	450W	57000	80	IES Type IV		
FL4-4504T4-2	277-480VAC	450W	57375	80	IES Type IV		

Note: All models are also available in an IES Type V configuration. Inquire for details.

Accessories



FL-MA4	Mounting Arm for FL4-Series Area Lights*
---------------	--



FL-MSC4-1	Integrated Motion Sensor for FL4-Series Area/Flood Lights (80W - 300W, 100-277V models only)
------------------	--



FL4-MSC4504-1	Integrated Motion Sensor for FL4-Series Area/Flood Lights (450W, 100-277V models only)
----------------------	--




PC1-TPT-1	Stem Mount Swivel Photocell (for 120V and Mounting Arm or Slip Fitter option only)
------------------	--



FL-SHIELD14	Glare Shield for FL4-Series Area/Flood Lights (80W/100/150W models only)
--------------------	--



FL-SHIELD24	Glare Shield for FL4-Series Area/Flood Lights (200W/240W/300W models only)
--------------------	--



FL-SHIELD34	Glare Shield for FL4-Series Area/Flood Lights (450W model only)
--------------------	---

* Other mounting options including Yoke, Trunnion, and Slip Fitter are also available. Inquire for details.