



Ultra-Slim Design

30W, 50W or 80W

100-277V

4000K



FLS1-Series Ultra-Slim Flood Lights



The FLS1-Series Flood Light is our line of ultra-slim LED flood lights designed for mounting on poles or walls to illuminate building perimeters, walkways, and landscapes or for wall graze and wall wash accent lighting.

With an IP65 rating and a minimum start temperature of -40° F/C, these low-profile floods are made with cold temperatures in mind.

Key Features & Benefits

- Designed for 100-277VAC applications
- Ultra low-profile and lightweight design lends to versatility
- Easily mounts on standard waterproof J-boxes
- Available in knuckle (30W model only) and yoke mount (30W, 50W and 80W versions)
- IP65 rated
- DLC-listed for high efficiency
- Worry-free 5 year warranty

WHY CHOOSE THIS FIXTURE?



WEATHERPROOF

Housed in an IP65 rated enclosure and designed to start even in -40 degree temperature

ULTRA-SLIM PROFILE

Fits into any application and unobtrusively blends in with the installed environment

PMMA LENS

Durable PMMA lens improves optics and adds to outdoor durability

KNUCKLE MOUNT*

Enables the flood light to be easily knuckle mounted

YOKE MOUNT

Allows the flood light to be surface mounted to the ground or wall

Available Models

MODEL#	VOLTAGE	WATTAGE	LUMEN	CRI	CCT	MOUNT TYPE
FLS1-304KN-1	100-277VAC	30W	2847 lm	81.9	4000K	Knuckle
FLS1-304TR-1	100-277VAC	30W	2847 lm	81.9	4000K	Yoke
FLS1-504TR-1	100-277VAC	50W	4700 lm	82.4	4000K	Yoke
FLS1-804TR-1	100-277VAC	80W	7716 lm	82.6	4000K	Yoke

*Knuckle mount version available only in 30W model.

Specifications and dimensions subject to change without notice.