



Lower Wattage, Higher Efficiency Offering

Unique, Long-Lasting Design

100-347V / 0-10V Dimming

3500K, 4000K & 5000K

FPH2-Series LED Hybrid Flat Panels



The FPH2-Series Hybrid LED Flat Panel ceiling light is a high performance LED panel that uses a unique back-lit design to provide a longer lasting lighting solution.

With a flicker-free, fully dimmable design that requires no warm-up, they produce very little heat and are the perfect replacement for traditional fluorescent lighting or low-end edge-lit flat panels found in offices, hospitals, schools and more.

Key Features & Benefits

- Back-lit design requires no light guide plate
- Lightweight design for quicker installs
- High-strength design resists bowing when hung
- Large junction box for quick and easy daisy chain connections
- 100-347V models make it easy to meet any job requirement
- Post-painted white frame
- Designed to fit directly into existing suspended T-bar ceilings
- Low profile: will fit into any plenum space
- Versatile installation options including hanging via aircraft cable or surface mounting (optional accessories)

WHY CHOOSE THIS FIXTURE?

SLIM PROFILE

Fits into any plenum space

LARGER JUNCTION BOX

A large 6" x 4" junction box leaves more room for connections and makes it easy to install

NO LIGHT GUIDE PLATE

Eliminates the potential of yellowing

WHITE POST-PAINTED FRAMES


Matches with any decor right out of the box

MULTIPLE MOUNTING OPTIONS

Ready to install into existing T-bars out of the box; or add accessories for additional mounting flexibility



Aircraft Cable Kit



Surface Mount Kit

Available Models

MODEL#	VOLTAGE	WATTAGE	LUMENS	EFFICACY	CCT	SIZE
FPH2-1430P35-3	100-347V	30W	3663 LM	126 lm/W	3500K	1 x 4
FPH2-1430P40-3	100-347V	30W	3728 LM	128 lm/W	4000K	1 x 4
FPH2-1430P50-3	100-347V	30W	3802 LM	131 lm/W	5000K	1 x 4
FPH2-2220P35-3	100-347V	20W	2656 LM	130 lm/W	3500K	2 x 2
FPH2-2220P40-3	100-347V	20W	2646 LM	136 lm/W	4000K	2 x 2
FPH2-2220P50-3	100-347V	20W	2743 LM	134 lm/W	5000K	2 x 2
FPH2-2230P35-3	100-347V	30W	3668 LM	127 lm/W	3500K	2 x 2
FPH2-2230P40-3	100-347V	30W	3705 LM	128 lm/W	4000K	2 x 2
FPH2-2230P50-3	100-347V	30W	3778 LM	131 lm/W	5000K	2 x 2
FPH2-2430P35-3	100-347V	30W	3721 LM	130 lm/W	3500K	2 x 4
FPH2-2430P40-3	100-347V	30W	3776 LM	133 lm/W	4000K	2 x 4
FPH2-2430P50-3	100-347V	30W	3851 LM	136 lm/W	5000K	2 x 4
FPH2-2440P35-3	100-347V	40W	4863 LM	128 lm/W	3500K	2 x 4
FPH2-2440P40-3	100-347V	40W	4912 LM	129 lm/W	4000K	2 x 4
FPH2-2440P50-3	100-347V	40W	5009 LM	131 lm/W	5000K	2 x 4
FPH2-2230S40-1	100-277V	30W	3000 LM	100 lm/W	4000K	2 x 2
FPH2-2440S40-1	100-277V	40W	4000 LM	100 lm/W	4000K	2 x 4

Optional Accessories

FPH-ACK11	Aircraft Cable for 1x4 and 2x2 Flat Panels	FPH-14SMK1	Surface Mount Kit for 1x4 Flat Panels
FPH-ACK21	Aircraft Cable for 2x4 Flat Panels	FPH-22SMK1	Surface Mount Kit for 2x2 Flat Panels
FHUPS1-UNV-25L-SD	Fulham Emergency Battery, Field Mount, 25W, 100-277V	FPH-24SMK1	Surface Mount Kit for 2x4 Flat Panels