

# LED Monopoint High Bays









The HBV1-Series is a monopoint high bay offering that combines performance and price to give you the best of both worlds.

With an efficacy of 150 lm/W, they are the perfect choice for applications where an economical solution is required.

## **Key Features & Benefits**

- Up to 150 lumens/W
- Offered in our most popular wattages: 100W, 150W, 200W, and 240W
- Available in both 100-277V or 120-347V with 1-10V dimming
- Includes a fixture hook with setscrew and 6-foot cord for easy installation

- IP65 rated for protection against water jet spray
- A native 110° beam angle works well with mid to high ceiling applications
- Aluminum and Prismatic 90° Reflectors available as additional accessories

### WHY CHOOSE THIS FIXTURE?

#### FIXTURE HOOK MOUNTING ...

Included fixture hook with setscrew prevents vibratory loosening when chain hanging (additional Carabiner accessory available as an option)


#### IP65 RATED······

Provides protection against water jets from any angle



## LOW PROFILE & LIGHTWEIGHT

For improved thermal performance and easy installation



#### **HIGH PERFORMANCE LEDs**

High output SMD 2835 LED chips for brighter, more efficient lighting

#### **REFLECTOR ACCESSORIES**

90° beam angle aluminum and prismatic reflectors available





100-277V Models									
MODEL#	VOLTAGE	WATTAGE	LUMEN	CRI	ССТ	OPERATION RANGE	DIMMING		
HBV1-1004-1	100-277V	100W	14,331 lm	80	4000K	-40°F to +122°F / -40°C to +50°C	1-10V		
HBV1-1005-1		100W	14,539 lm		5000K				
HBV1-1504-1		150W	21,791 lm		4000K				
HBV1-1505-1		150W	22,030 lm		5000K				
HBV1-2004-1		200W	29,500 lm		4000K				
HBV1-2005-1		200W	29,912 lm		5000K				
HBV1-2404-1		240W	34,986 lm		4000K				
HBV1-2405-1		240W	35,487 lm		5000K				

120-347V Models									
MODEL#	VOLTAGE	WATTAGE	LUMEN	CRI	ССТ	OPERATION RANGE	DIMMING		
HBV1-1004-3	120-347V	100W	14,953 lm	80	4000K	-40°F to +122°F / -40°C to +50°C	1-10V		
HBV1-1005-3		100W	15,169 lm		5000K				
HBV1-1504-3		150W	22,089 lm		4000K				
HBV1-1505-3		150W	22,332 lm		5000K				
HBV1-2004-3		200W	29,749 lm		4000K				
HBV1-2005-3		200W	30,119 lm		5000K				
HBV1-2404-3		240W	35,864 lm		4000K				
HBV1-2405-3		240W	36,295 lm		5000K				

Available Accessories				
MODEL#	DESCRIPTION			
HBV-REF1-AL-90	90 degree aluminum reflector for HBV1 High Bays 100W / 150W models			
HBV-REF2-AL-90	90 degree aluminum reflector for HBV1 High Bays 200W / 240W models			
HBV-REF1-PC-90	90 degree prismatic reflector for HBV1 High Bays 100W / 150W models			
HBV-REF2-PC-90	90 degree prismatic reflector for HBV1 High Bays 200W / 240W models			
HB-CARABINER	Carabiner for suspending HBV1 High Bays			
FHUPS1-UNV-25L-SD	Fulham Emergency Battery, Field Mount, 25W, 100-277V			