



# F32T8/835K



<b>Description</b>	32W Universal Start 3500K 85 CRI T-8 Medium Bi-pin
<b>Ordering Code</b>	49588
<b>UNSPSC Code</b>	39101605

## Specifications

<b>Watts</b>	32
<b>Base Type</b>	G13
<b>Bulb Type</b>	T8
<b>MOL in/mm</b>	47.99/1,219.00
<b>Length</b>	4'
<b>MOD in/mm</b>	1.02/26.00
<b>Mercury Content (mg)</b>	3
<b>HG Form</b>	solid
<b>Approx Initial Lumens</b>	2,950
<b>Approx Mean Lumens</b>	2,800
<b>CCT</b>	3500
<b>CRI</b>	85
<b>Rated Life</b>	24,000
<b>Avg Life 3 HR Inst Start</b>	24,000
<b>Avg Life 3 HR Prog Start</b>	30,000
<b>Avg Life 12 HR Inst Start</b>	30,000
<b>Avg Life 12 HR Prog Start</b>	36,000
<b>Special Desc</b>	Three Phosphor, Universal Start
<b>Approvals</b>	IMERC, TCLP Compliant
<b>California Title 20</b>	Exempt

**connected solutions. service. simplicity. eiko.com**

18000 W. 105<sup>th</sup> Street, 3<sup>rd</sup> Floor, Olathe, KS 66061 (P) 1.800.852.2217 (F) 1.800.492.8975  
EiKO Canada: 81 King Street, Barrie, ON L4N 6B5 (P) 1.888.410.8151 (F) 1.888.705.1335