



## EXIT/EMERGENCY

### FEATURES

- Easy to install
- Long battery life
- Environmentally friendly
- Energy saving
- Single or double-sided installation

### LISTINGS

- UL Listed for Dry/Damp locations
- Safety and performance in accordance with UL-924

### PERFORMANCE

- ≥90 minutes of emergency operating power at the rated wattage

### ELECTRICAL SPECIFICATIONS

- Input voltage: 120/347V
- Input power: 3W
- Power Factor: >0.5
- Emergency operation: ≥90 mins
- Recharge: 24 hrs

### THERMAL

- 32°F to 104°F (0°C to 40°C) operating temperature

### CONSTRUCTION

- Injection molded ABS and polycarbonate housings

### WARRANTY

- 3 year limited warranty; see eiko.com for warranty details

project name	type
catalog number	
comments	voltage
approved by	date



EXIT/CA



EXIT/EM/CA

Included Faceplates:



### APPLICATIONS

- Emergency and exit lighting

RoHS  
Compliant

FC

cUL  
LISTED

## ORDERING INFORMATION

EXAMPLE: EXIT/EM-R-BK

### Model

EXIT/CA - Exit Sign

EXIT/EM/CA - Exit Sign with Emergency Light

## PERFORMANCE SUMMARY

Order Code	Item #	Lumens	Description
11049	EXIT/CA	100	Exit Sign (Canada)
11050	EXIT/EM/CA	100	Exit Sign with Emergency Light (Canada)

## DIMENSIONS

