



## DDS : DISK DOWNLIGHT SURFACE

### DESCRIPTION

A two-in-one downlight solution that can be retrofitted into an existing can or surface mounted to a 3"/4"/5"/6" junction box. Easy to install and economical to operate, providing smooth, even light with no dark spots.

### FEATURES

- Low profile, driverless design
- Continuous dimming from 10-100% with many Triac dimmers
- Retrofits into an existing recessed can with available accessory

### LISTINGS

- ETL Listed for Wet Locations
- Select models can be used to comply with Title 24/Title20/JA8

### PERFORMANCE

- Rated lifetime L70: 35,000 hours
- 3000K CCT; 27/30/40K Selectable CCT
- CRI: 80+; 90+

### ELECTRICAL

- Input voltage: 120V
- Power Factor: >.90

### CONSTRUCTION

- -4°F to 104°F (-20°C to 40°C) operating temperature

### WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

project name	type
catalog number	
comments	voltage
approved by	date



### APPLICATIONS

- Healthcare
- Hospitality
- Office
- Property Management
- Residential
- Retail



## ORDERING INFORMATION

EXAMPLE: DDS6-100-15W-830-120-DT-WH-D

Model	Size	Lumens	Wattage	CRI/CCT	Voltage	Dimming	Finish	Generation
DDS : Disk Downlight Surface	4 - 4"	70 - 700 lm	10W - 10W	830 - 80 CRI; 3000K	120 - 120V	DT - Triac Dimming	WH - White	Blank - Black
		55 - 550 lm		9CCT3 - 90 CRI; 27/30/4000K				
	6 - 6"	100 - 1,000 lm	15W - 15W	830 - 80 CRI; 3000K				
		82 - 825 lm		9CCT3 - 90 CRI; 27/30/4000K				
	8 - 8"	121 - 1,210 lm	20W - 20W	9CCT3 - 90 CRI; 27/30/4000K				
	4 - 4"	70 - 700 lm	10W - 10W	830 - 80 CRI; 3000K				D - Gen
6 - 6"	100 - 1,000 lm	15W - 15W						

## PERFORMANCE SUMMARY

Order Code	Item #	Size	Watts	Lumens	CCT	CRI	Volts	T20/JA8	ES
11236	DDS4-70-10W-830-120-DT-WH	4"	10W	800	3000K	80+	120V		
11224	DDS6-100-15W-830-120-DT-WH	6"	15W	1,000	3000K	80+	120V		
11225	DDS4-55-10W-9CCT3-120-DT-WH	4"	10W	550	27/30/40K	90+	120V	✓	★
11226	DDS6-82-15W-9CCT3-120-DT-WH	6"	15W	820	27/30/40K	90+	120V	✓	★
11227	DDS8-121-20W-9CCT3-120-DT-WH	8"	20W	1,210	27/30/40K	90+	120V	✓	★
12777	DDS4-70-10W-830-120-DT-WH-D	4"	10W	800	3000K	80+	120V		★
12778	DDS6-100-15W-830-120-DT-WH-D	6"	15W	1,000	3000K	80+	120V		★

★ENERGY STAR® Approved

## ACCESSORIES

Order Code	Item #	Size
11228	DDS4RETROACC	4" Retrofit Accessory
11229	DDS6RETROACC	6" Retrofit Accessory

## DIMENSIONS

