



## ELEVATOR LIGHTS

### DESCRIPTION

3W LED replacement lamp for elevators and other small applications.

### FEATURES

- Instant-on with no warmup
- Lasts 20x longer than incandescent for reduced replacement and maintenance costs
- Uses up to 90% less energy than incandescent or halogen
- Shatter-resistant for reduced risk of injury and breakage

### WARRANTY

- 3 year limited warranty; see eiko.com for warranty details

### APPLICATIONS

- Elevators
- Property Management
- Hospitality
- Retail
- Aircraft
- Hospitals
- Office Lighting
- Shopping Malls
- Parking Garages



RoHS  Compliant

<b>PERFORMANCE</b>	Power Consumption	3W
	Lumens	125
	Efficacy (LPW)	42
	CRI	70+
	CCT	3000K, 4000K
	Life (L70)	20,000/30,000 hours
<b>ELECTRICAL</b>	Power Factor	≥0.9
	THD	<20%
<b>CONSTRUCTION</b>	Base	BA15d, BA15s
<b>LISTINGS</b>	Material Usage	RoHS Compliant; no mercury or lead

## PERFORMANCE SUMMARY

### GBF NON-DIMMABLE BA15D BASE - 12V AC/DC:

Order Code	Item #	Lumens	Watts	CCT	CRI	Beam	MOL	Life/Hours	Replaces Halogen
08895	LED3WGBF/30/830-G5	125	3W	3000K	80+	30°	1.77"	20,000	20W GBF
08900	LED3WGBF/30/840-G5	125	3W	4000K	75+	30°	1.77"	20,000	20W GBF

### 1383 NON-DIMMABLE BA15S BASE - 12V AC/DC:

Order Code	Item #	Lumens	Watts	CCT	CRI	Beam	MOL	Life/Hours	Replaces Halogen
08896	LED3W1383/30/830-G5	125	3W	3000K	80+	30°	2.48"	20,000	20W 1383
08899	LED3W1383/30/840-G5	125	3W	4000K	75+	30°	2.48"	20,000	20W 1383

NOTE: Use order code when ordering.

## DIMENSIONS

