



## STR-R Linear Strip Retrofit

### FEATURES

- Designed for easy installation on existing fluorescent strip fixtures, providing a quick update to the latest in LED performance without the need for all-new fixtures
- Available for 4' and 8' applications
- Designed for fixtures between 4.25" and 5.25" wide
- Up to 50% energy savings over fluorescent fixtures
- Up to 130 lpw
- PowerSet feature allows for multiple "set and forget" lumen stops in each fixture
- FieldCCeT feature allows for multiple "set and forget" CCT options in each fixture

### CERTIFICATIONS

- UL Listed for dry/damp locations
- DesignLights Consortium® Qualified - meets DLC requirements for efficacy and lumen maintenance

### PERFORMANCE

- Rated lifetime:
  - L90: >50,000 hours @25°C
- 3500K and 4000K CCT
- FieldCCeT: 35/40/5000K CCT
- CRI: >80
- PowerSet:
  - 4': 44/35/27/22W; 5,850/4,550/3,500/2,850 lm
  - 8': 88/68/54W; 11,400/8,800/7000 lm

### ELECTRICAL

- Input voltage: 120-277V; 120-347V
- 0-10V dimming to <5% with dim-to-off capability
- 12Vdc, 60mA power for controls
- Power Factor: >0.9
- THD: <20%

### THERMAL

- -22°F to 122°F (-30°C to 50°C) operating temperature

### CONSTRUCTION

- Die-formed cold rolled steel with gloss white powder coated finish
- Extruded acrylic lens for uniform illumination and visual comfort
- 1/2" trade KOs on both ends

### WARRANTY

- 5 Year limited warranty available [online](#). Contact your EiKO sales rep for additional details.

project name	type
catalog number	voltage
approved by	date



STR4R



STR8R



### APPLICATIONS

- Storage areas
- Utility areas
- Coves
- Display cases
- Retail
- Task lighting
- General area lighting

## AVAILABLE MODELS

ORDER	ORDER CODE	ITEM #	LENGTH	WATTS	CCT	LUMENS	EFFICACY (lm/W)	CRI	VOLTAGE	DIMMING	DLC
											STANDARD
	11362	STR4R/PS44/835/UD	4'	44/35/27/22W	3500K	5850/4550/3500/2850 lm	130 lm/W	>80	120-277V	0-10V	PP4W25PL
	11363	STR4R/PS44/840/UD	4'	44/35/27/22W	4000K	5850/4550/3500/2850 lm	130 lm/W	>80	120-277V	0-10V	PB691L52
	11364	STR4R/PS44/FCCT/UD	4'	44/35/27/22W	35/40/5000K	5850/4550/3500/2850 lm	130 lm/W	>80	120-277V	0-10V	PL10DLH0
	11366	STR8R/PS88/835/UD	8'	88/68/54W	3500K	11,400/8800/7000 lm	130 lm/W	>80	120-277V	0-10V	PTFA68IG
	11367	STR8R/PS88/840/UD	8'	88/68/54W	4000K	11,400/8800/7000 lm	130 lm/W	>80	120-277V	0-10V	PJGY6FP
	11368	STR8R/PS88/FCCT/UD	8'	88/68/54W	35/40/5000K	11,400/8800/7000 lm	130 lm/W	>80	120-277V	0-10V	P1XGW0UI
<b>CANADA ONLY</b>											
	11365	STR4R/PS44/FCCT/HD	4'	44/35/27/22W	35/40/5000K	5850/4550/3500/2850 lm	130 lm/W	>80	120-347V	0-10V	PUHZ9W0L

## FACTORY INSTALLED OPTIONS

BATTERY BACKUP	CONTROLS
<p><b>[Blank]</b> : Default, no additional protection</p> <p><b>EM8W</b> : 8W Internal Backup battery, 120-277V</p> <p><b>EM15W</b> : 15W Internal Backup battery, 120-277V</p> <p><b>EM20W</b> : 20W Internal Backup battery, 120-277V</p>	<p><b>[Blank]</b> : Default, no controls</p> <p><b>M01</b> : Stand-alone 1/2" Knock-out PIR Motion Sensor, 8-40ft</p> <p><b>M09</b> : Stand-alone 1/2" Knock-out Microwave Motion Sensor, 8-40ft</p> <p><b>M10</b> : Stand-alone 1/2" Knock-out PIR Motion Sensor, 8-40ft</p> <p><b>M18</b> : Stand-alone 1/2" Knock-out PIR Motion Sensor, 8-35ft</p> <p><b>M19</b> : Stand-alone 1/2" Knock-out PIR Motion Sensor, 8-35ft</p> <p><b>M19</b> : Stand-alone 1/2" Knock-out PIR Motion Sensor, 8-35ft</p> <p><b>M20</b> : Stand-alone Microwave Motion Sensor, 8-48ft</p>

## MODEL CONFIGURATOR

## FACTORY INSTALLED OPTIONS

MODEL	-	SIZE	-	WATTS	-	CCT	-	VOLTAGE	-	BATTERY BACKUP	-	CONTROLS
<b>STR</b>	-		-		-		-		-		-	

EXAMPLE PART NUMBER: STR-4R-PS44-835-UD-EM8W

REFER TO FOLLOWING SECTIONS FOR DETAILS ON FACTORY INSTALLED OPTIONS & AVAILABLE FIELD INSTALLED OPTIONS

## BATTERY BACKUPS

ORDER	ORDER CODE	ITEM #	DESCRIPTION	FACTORY INSTALLED CODE
	10918	EEBN08WUA050*	EiKO Emergency Battery Kit Internal 8W 120-277VAC 25-50VDC CEC Compliant. Factory or Field Installed Only.	EM8W
	10896	EEBN15WUA050*	EiKO Emergency Battery Kit Internal 15W 120-277VAC 25-50VDC CEC Compliant. Factory or Field Installed Only.	EM15W
	10897	EEBN20WUA050*	EiKO Emergency Battery Kit Internal 20W 120-277VAC 25-50VDC CEC Compliant. Factory or Field Installed Only.	EM20W


## CONTROLS & SENSORS

ORDER	ORDER CODE	ITEM #	DESCRIPTION	FACTORY INSTALLED CODE
<b>STANDALONE CONTROLS</b>				
<b>PIR SENSORS</b>				
	800654	MS2-OPD-3	Stand-alone PIR Motion Sensor, 120-347V, 1/2" knock-out, On/Off, Ambient Threshold, 40ft, Parameters set by dip switch. Order separately.	M1
	800655	MS2-DPX-3	Stand-alone PIR Motion Sensor, 120-347V, 1/2" knock-out, 0-10V, Ambient Threshold, 40ft, Parameters set by dip switch or RC-100/SEN5A-ACT. Order separately.	M10
	10220	SEN-3B-KO	Stand-alone PIR Motion Sensor, 120-277V, IP66, 1/2" knock-out, 0-10V, Ambient Threshold, 30ft, Parameters set by SEN-3-RC.	M18
	10476	SEN-3A-KO	Stand-alone PIR Motion Sensor, 120-277V, IP66, 1/2" knock-out, On/Off, Ambient Threshold, 30ft, Parameters set by dip switch.	M19
	10476	SEN-3AA-KO	Stand-alone PIR Motion Sensor, 120-277V, 1/2" knock-out, On/Off, Ambient Threshold, 30ft, Parameters set by dip switch.	M19


## CONTROLS & SENSORS CONT'D

ORDER	ORDER CODE	ITEM #	DESCRIPTION	FACTORY INSTALLED CODE
<b>STANDALONE CONTROLS</b>				
<b>MICROWAVE SENSORS</b>				
	313895	MS1-DHR-KO-1	Stand-alone Microwave Motion Sensor, 120-277V, IP65, 1/2" knock-out, 0-10V, Ambient Threshold, 48ft, Parameters set by RC01.	M20
	12150	SEN/M/S1C/KO	Stand-alone Microwave Motion Sensor, 120-277V, IP65 1/2" knock-out, 0-10V, Ambient Threshold, Parameters set by SEN-S1-RC3.	M09
<b>REMOTES FOR COMMISSIONING STANDALONE CONTROLS</b>				
	13344	SEN5A-ACT	Commissioning Tool for SEN5A, BAY-E-SEN/PIR, BAY-E-SEN/M, and MS2-DPX-3 (Backward compatible with SEN5A/CT and RC-100).	---
	10226	SEN-3-RC	Commissioning Tool for SEN-3B-KO and SEN-3C-KO.	---
	313897	RC01	Commissioning Tool for MS1-DHR-SA-4, MS1-DHR-KO-1, MS1-DHR-KO-4.	---
	10917	SEN-S1-RC3	Commissioning Tool for SEN/M/S1C/KO.	---
<b>ADAPTERS &amp; ACCESSORIES</b>				
	12634	PSC-WCM-450-BLE-SR	"BLE TruBlu Wireless Control Module, 120-277V, 16A Relay, 0-10V, 12V AUX 300mA, 100ft"	---

## PRODUCT DIMENSIONS



**STR4R**




**STR8R**

## PHOTOMETRICS


**STR4R/PS44/840/UD** (Typical performance @44W, 4000K)

ZONAL LUMEN SUMMARY		
ZONE	LUMENS	%FIXTURE
0-30	1513.3	24.4%
0-40	2472.23	39.9%
0-60	4406.94	71.2%
0-80	5817.19	94.0%
0-90	6190.35	100%




**STR4R/PS44/FCCT/UD** (Typical performance @44W, 4000K)

ZONAL LUMEN SUMMARY		
ZONE	LUMENS	%FIXTURE
0-30	1513.3	24.4%
0-40	2472.23	39.9%
0-60	4406.94	71.2%
0-80	5817.19	94.0%
0-90	6190.35	100%




**STR8R/PS88/840/UD** (Typical performance @88W, 4000K)

ZONAL LUMEN SUMMARY		
ZONE	LUMENS	%FIXTURE
0-30	3127.49	25.0%
0-40	5109.02	40.9%
0-60	9087.93	72.7%
0-80	11839.24	94.8%
0-90	12492.53	100%



**STR8R/PS88/FCCT/UD** (Typical performance @88W, 4000K)

ZONAL LUMEN SUMMARY		
ZONE	LUMENS	%FIXTURE
0-30	3127.49	25.0%
0-40	5109.02	40.9%
0-60	9087.93	72.7%
0-80	11839.24	94.8%
0-90	12492.53	100%



## SCALING FACTORS

FIXTURE	POWERSET		FIELDCCET			
	WATTS	3500K 4000K	3500K	4000K	5000K	
4'	44	1.00	0.95	1.00	0.97	
	35	0.85	0.80	0.83	0.82	
	27	0.64	0.62	0.64	0.63	
	22	0.51	0.49	0.50	0.49	
8'	88	1.00	0.93	1.00	0.97	
	68	0.76	0.72	0.76	0.75	
	54	0.60	0.57	0.59	0.59	