



project name	type
catalog number	voltage
approved by	date

JL NEMA TWIST-LOCK PHOTOCELLS

PHOTOCELLS

ORDER	ORDER CODE	ITEM #	DESCRIPTION	IMAGE
	14947	JL-205C	<p>Style: 3-pin NEMA Twist-Lock On/Off Photocell Input Voltage: 120-277V, 50/60Hz Max Current: 5A Power Restriction: load must be >120W On Level: 6 Lx Off Level: 50 Lx Ambient Temperature: -40°F to 158°F (-40°C to 70°C) IP Rating: IP67 Certifications: ANSI C136.10-2010, UL Certified for US & Canada Warranty: 2 years</p>	
	14948	JL-207C	<p>Style: 3-pin NEMA Twist-Lock On/Off Photocell Input Voltage: 120-277V, 50/60Hz Max Current: 5A On Level: 16 Lx Off Level: 24 Lx Ambient Temperature: -40°F to 158°F (-40°C to 70°C) IP Rating: IP67 Certifications: ANSI C136.10-2010, UL Certified for US & Canada Warranty: 5 years</p>	
	14949	JL-207F	<p>Style: 3-pin NEMA Twist-Lock On/Off Photocell Input Voltage: 120-480V, 50/60Hz Max Current: 5A On Level: 16 Lx Off Level: 24 Lx Ambient Temperature: -40°F to 158°F (-40°C to 70°C) IP Rating: IP65 Certifications: ANSI C136.10-2010, UL Certified for US & Canada Warranty: 5 years</p>	
	14950	JL-208	<p>Style: Shorting Cap Input Voltage: 120-480V, 50/60Hz Max Current: 15A Ambient Temperature: -40°F to 158°F (-40°C to 70°C) IP Rating: IP66 Certifications: ANSI C136.10-2010, UL Certified for US & Canada Warranty: 2 years</p>	
	801337	JL-242C	<p>Style: 5-pin NEMA Twist-Lock Dimming Photocell Input Voltage: 120-277V, 50/60Hz Max Current: 5A On Level: 50 Lx Off Level: 50 Lx Ambient Temperature: -40°F to 158°F (-40°C to 70°C) IP Rating: IP65 Certifications: ANSI C136.41-2013, UL Certified for US & Canada Warranty: 5 years</p>	
	801338	JL-242F	<p>Style: 5-pin NEMA Twist-Lock Dimming Photocell Input Voltage: 347-480V, 50/60Hz Max Current: 2A On Level: 50 Lx Off Level: 50 Lx Ambient Temperature: -40°F to 158°F (-40°C to 70°C) IP Rating: IP65 Certifications: ANSI C136.41-2013, UL Certified for US & Canada Warranty: 5 years</p>	