

# WFC1 | Full Cutoff Wall Pack

#### HIGHLIGHTS

- Full cutoff optics to reduce glare, light pollution and improve visibility
- Hinged junction box makes installation and maintenance easier
- Multiple knockouts available for various installations
- Leveling made easy with internal level Integrated photocell for dusk to dawn operation
- PowerSet feature allows for multiple "set and forget" lumen stops in each fixture
- FieldCCeT feature allows for multiple "set and forget" CCT options in each fixture

#### **CERTIFICATIONS**

- ETL listed for US & Canada
- RoHS compliant FCC compliant
- ICES-005 compliant
- IP65 Rated
- IK10 Impact Rating
- DesignLights Consortium® Premium Qualified meets the requirements for the highest DLC qualification for efficacy and lumen maintenance
- DesignLights Consortium® Luna (Model #14557)

## **PERFORMANCE**

- High efficacy, up to 130 lm/W
- Available in PowerSet model: power-selectable 70/60/45W
- Available in single CCT models: 3000K or FieldCCeT models: field-selectable CCT 30/40/5000K
- CRI: >80
- Beam Angle: NEMA 7H x 6V
- Rated Life: >54.000 Hours

#### **ELECTRICAL**

- Input voltage: 120-347V
- 0-10V dimming, dim-to-off
- Surge protection: 4kV
- Power factor: >0.9 THD: <20%.

## **THERMAL**

-40°F to 104°F (-40°C to 40°C) operating temperature

#### CONSTRUCTION

- Bronze powder coated, die-cast aluminum housing
- Impact resistant polycarbonate lens
- IK10 impact rating

#### DIMMING

For dimming compatibility visit eiko.com

#### WARRANTY

• 5-Year limited warranty available online. Contact your EiKO sales rep for additional details.

project name	type		
catalog number	voltage		
approved by	date		

























#### **APPLICATIONS**

- Industrial Parks
- Loading Docks
- Utility Sheds Entryways
- Walkways Storage Areas
- Security

#### **KEY FEATURES**

# SELECTABLE CCT AND WATTAGE

Choose your CCT and Wattage upon install; great for SKU reduction and job site flexibility

#### **INSTALLATIONS MADE EASY**

Mounts directly to junction box or there are multiple knockouts for conduit wiring. Internal level helps ensure precision leveling and hinged door makes maintenance easy

### **DESIGNED WITH THE ENVIRONMENT IN MIND**

Powder coated, die-cast aluminum housing, impact resistant polycarbonate. Full cutoff optics reduce glare, light pollution, and improves visibility (DLC LUNA Model #14557)











## **AVAILABLE MODELS**


	ORDER CODE	ITEM #	WATTS*	CCT**	LUMENS	EFFICACY (Im/W)	VOLTAGE	TRADITIONAL WATTAGE EQUIVALENT	DLC ID #
ORDER									PREMIUM
	13461	WFC1-PS70-FCCT-H	70/60/45W	30/40/5000K	9100/7800/5850 lm	130 lm/W	120-347V	Up to 250W HID	S-5AQYOW
	14557	WFC1-PS70-30-H***	70/60/45W	3000K	9100/7800/5850 lm	130 lm/W	120-347V	Up to 250W HID	S-FX46E2


<sup>\*</sup> All power-selectable fixtures ship at the highest wattage setting \*\* All CCT-selectable fixtures ship at 3000K \*\*\* Model for DLC Luna

	MODEL CONFIGURATOR							
N	ODEL	-	WATTAGE	-	сст	-	VOLTAGE	
	WFC1	-		-		-		

**EXAMPLE PART NUMBER: WFC1-PS70-FCCT-H** 

## **PRODUCT DIMENSIONS**





6.8" / 173mm

WFC1- ALL MODELS

Weight: 5.29 lbs / 2.4 kg