



A-Shape A15 and A19 LED Lamps

HIGHLIGHTS

- A-Shape lamps are the energy efficient, dimmable replacements for classic incandescent, halogen, and CFL bulbs
- Long lifespan (up to 25,000 hours) minimizes replacement and maintenance costs
- Wide range of bases available to suit your project needs: E12, E17, E26, and GU24
- Polycarbonate frosted lens provide diffused lighting and reduces the risk of injury and breakage
- Clear glass lamps provide a brighter, visual sparkle and are ideal for fixtures without shades to enhance the ambience of any room
- High CRI models available for lighting up objects in their true and natural color
- Ideal for both residential and commercial settings

CERTIFICATIONS

- UL Listed for Damp or Wet Locations*
- Energy Star rated
- RoHS Compliant
- FCC Compliant
- Title 20/JA8 Certified**

PERFORMANCE

- High efficacy: up to 123 lm/W
- Single CCT models are available
- FieldCCT: 2700/3000/4000/5000K
- CRI: up to 90 CRI
- Rated Lifetime (based on model): up to 25,000 hours

ELECTRICAL

- Input voltage: 120V
- Input frequency: 60Hz
- Smooth Triac dimming down to 10%

THERMAL

- -4°F to 104°F (-20°C to 40°C) operating temperature***

CONSTRUCTION

- Plastic models are constructed from frosted, shatter-resistant polycarbonate
- Glass models use a clear glass finish to emulate a traditional look and feel

DIMMING COMPATABILITY

- For a list of compatible dimmers please visit eiko.com

WARRANTY

- Up to 3 Year limited warranty available (based on each model's Rated Lifetime). Please see our warranty [online](#) or contact your EiKO sales rep for additional details.

*Wet or Dry Location rating dependent on model

**Title 20/JA8 Certification dependent on model

***Not recommended for air-tight fixtures

project name	type
catalog number	voltage
approved by	date



A15 - PLASTIC
E12 BASE



A15 - PLASTIC
E17 BASE



A15 - PLASTIC
E26 BASE



A15 - GLASS
E26 BASE



A19 - PLASTIC
E26 BASE



A19 - PLASTIC
GU24 BASE



A19 - GLASS
E26 BASE



A19 - GLASS
(FIELD CCT)
E26 BASE

For illustration purposes only. The look of each model may vary slightly based on wattage. See the Product Dimensions section for details.



KEY FEATURES

A15 OR A19 SHAPE

A15 or A19-Shape lamps ensure you find the best size and look for installing into your fixtures



E12 BASE



E17 BASE



E26 BASE




GU24 BASE

WIDE RANGE OF BASES

Select from a wide range of bases to suit your project needs: E12, E17, E26 or GU24

HIGH CRI

90 CRI models to more accurately reproduce the colors of the objects they illuminate



AVAILABLE MODELS

ORDER CODE	ITEM #	BASE TYPE	WATTS	LUMENS	CCT	EFFICACY (lm/W)	CRI	RATED LIFE (HRS)	DIMMABLE	TRADITIONAL WATTAGE EQUIVALENT	LOCATION RATING	T20/JA8	IMAGE
A15 - PLASTIC													
13035	L6WA15/830PF/D/E12	E12	6	450	3000	75	80	10,000		40	Damp		A
13061	L8WA15/830PF/D/E12	E12	8	800	3000	100	80	15,000	✓	60	Damp		A
13050	L6WA15/830PF/D/E17	E17	6	450	3000	75	80	10,000		40	Damp		B
13032	L8WA15/830PF/D/E17	E17	8	800	3000	100	80	15,000	✓	60	Damp		B
13044	L5.5WA15/830PF/D/E26	E26	5.5	450	3000	82	80	15,000	✓	40	Damp		C
13036	L8WA15/830PF/D/E26	E26	8	800	3000	100	80	15,000	✓	60	Damp		C
A19 - PLASTIC													
13063	L5.5WA19/827PF/D/E26	E26	5.5	450	2700	82	80	25,000	✓	40	Damp		D
13062	L5.5WA19/830PF/D/E26	E26	5.5	450	3000	82	80	25,000	✓	40	Damp		D
13023	L5.5WA19/840PF/D/E26	E26	5.5	450	4000	82	80	25,000	✓	40	Damp		D
13054	L8WA19/827PF/D/E26	E26	8	800	2700	100	80	25,000	✓	60	Damp		D
13019	L8WA19/830PF/D/E26	E26	8	800	3000	100	80	25,000	✓	60	Damp		D
13038	L8WA19/840PF/D/E26	E26	8	800	4000	100	80	25,000	✓	60	Damp		D
13020	L9WA19/830PF/E26	E26	9	800	3000	89	80	10,000		60	Damp		K
13034	L9WA19/840PF/E26	E26	9	800	4000	89	80	10,000		60	Damp		K
13043	L9WA19/850PF/E26	E26	9	800	5000	89	80	10,000		60	Damp		K
13051	L9WA19/930PF/D/E26	E26	9	810	3000	90	90	25,000	✓	60	Damp	✓	N
13059	L9WA19/940PF/D/E26	E26	9	810	4000	90	90	25,000	✓	60	Damp	✓	N
13030	L11WA19/827PF/D/E26	E26	11	1100	2700	100	80	25,000	✓	75	Damp		E
13039	L11WA19/830PF/D/E26	E26	11	1100	3000	100	80	25,000	✓	75	Damp		E
13012	L11WA19/840PF/D/E26	E26	11	1100	4000	100	80	25,000	✓	75	Damp		E
13065	L12A19/930PF/D/E26	E26	12	1100	3000	92	90	25,000	✓	75	Damp	✓	N
13022	L12A19/940PF/D/E26	E26	12	1100	4000	92	90	25,000	✓	75	Damp	✓	N
13015	L12WA19/830PF/E26	E26	12	1050	3000	88	80	10,000		75	Damp		K
13013	L12WA19/840PF/E26	E26	12	1050	4000	88	80	10,000		75	Damp		K
13064	L12WA19/850PF/E26	E26	12	1050	5000	88	80	10,000		75	Damp		K
13053	L13WA19/827PF/D/E26	E26	13	1600	2700	123	80	25,000	✓	100	Damp		F
13028	L13WA19/830PF/D/E26	E26	13	1600	3000	123	80	25,000	✓	100	Damp		F
13056	L13WA19/840PF/D/E26	E26	13	1600	4000	123	80	25,000	✓	100	Damp		F
13060	L14A19/930PF/D/E26	E26	14	1600	3000	114	90	15,000	✓	100	Damp	✓	F
13037	L14A19/940PF/D/E26	E26	14	1600	4000	114	90	15,000	✓	100	Damp	✓	F
13049	L15WA19/830PF/E26	E26	15	1500	3000	100	80	10,000		100	Damp		L
13041	L15WA19/840PF/E26	E26	15	1500	4000	100	80	10,000		100	Damp		L
13055	L15WA19/850PF/E26	E26	15	1500	5000	100	80	10,000		100	Damp		L
13057	L9WA19/930PF/D/GU24	GU24	9	810	3000	90	90	25,000	✓	60	Damp	✓	M
13052	L9WA19/940PF/D/GU24	GU24	9	810	4000	90	90	25,000	✓	60	Damp	✓	M
13042	L12WA19/930PF/D/GU24	GU24	12	1100	3000	92	90	25,000	✓	75	Damp	✓	M
13066	L12WA19/940PF/D/GU24	GU24	12	1100	4000	92	90	25,000	✓	75	Damp	✓	M
A19 - PLASTIC - DUSK TO DAWN													
15624	L6WA19/830PF/E26/DTD	E26	6	800	3000	133	80	15,000		60W	Damp		J
15625	L6WA19/840PF/E26/DTD	E26	6	800	4000	133	80	15,000		60W	Damp		J
15626	L6WA19/850PF/E26/DTD	E26	6	800	5000	133	80	15,000		60W	Damp		J

ORDER CODE	ITEM #	BASE TYPE	WATTS	LUMENS	CCT	EFFICACY (lm/W)	CRI	RATED LIFE (HRS)	DIMMABLE	TRADITIONAL WATTAGE EQUIVALENT	LOCATION RATING	T20/JA8	IMAGE
A15 - GLASS													
13017	L2.5WA15/827GC/D/E26	E26	2.5	250	2700	100	80	15,000	✓	25	Wet		G
13018	L4.5WA15/827GC/D/E26	E26	4.5	450	2700	100	80	15,000	✓	40	Wet		H
13025	L7WA15/827GC/D/E26	E26	7	800	2700	114	80	15,000	✓	60	Wet		H
A19 - GLASS													
13027	L4.5WA19/827GC/D/E26	E26	4.5	450	2700	100	80	15,000	✓	40	Wet		I
13046	L4.5WA19/830GC/D/E26	E26	4.5	450	3000	100	80	15,000	✓	40	Wet		I
13048	L4.5WA19/840GC/D/E26	E26	4.5	450	4000	100	80	15,000	✓	40	Wet		I
13040	L7WA19/827GC/D/E26	E26	7	800	2700	114	80	15,000	✓	60	Wet		I
13047	L7WA19/830GC/D/E26	E26	7	800	3000	114	80	15,000	✓	60	Wet		I
13029	L7WA19/840GC/D/E26	E26	7	800	4000	114	80	15,000	✓	60	Wet		I
13026	L8.5WA19/927GC/D/E26	E26	8.5	800	2700	94	90	15,000	✓	60	Wet	✓	I
13045	L8.5WA19/930GC/D/E26	E26	8.5	800	3000	94	90	15,000	✓	60	Wet	✓	I
13011	L10WA19/827GC/D/E26	E26	10	1100	2700	110	80	15,000	✓	75	Wet		I
13014	L10WA19/830GC/D/E26	E26	10	1100	3000	110	80	15,000	✓	75	Wet		I
13021	L10WA19/840GC/D/E26	E26	10	1100	4000	110	80	15,000	✓	75	Wet		I
13024	L10WA19/927GC/D/E26	E26	10	1100	2700	110	90	15,000	✓	75	Wet	✓	I
13033	L10WA19/930GC/D/E26	E26	10	1100	3000	110	90	15,000	✓	75	Wet	✓	I
13058	L13WA19/827GC/D/E26	E26	13	1600	2700	123	80	15,000	✓	100	Wet		I
13016	L13WA19/830GC/D/E26	E26	13	1600	3000	123	80	15,000	✓	100	Wet		I
13031	L13WA19/840GC/D/E26	E26	13	1600	4000	123	80	15,000	✓	100	Wet		I

ORDER CODE	ITEM #	FINISH	WATTS	LUMENS	CCT	EFFICACY (lm/W)	CRI	RATED LIFE (HRS)	DIMMABLE	TRADITIONAL WATTAGE EQUIVALENT	LOCATION RATING	IMAGE
A19 FIELDCCeT - GLASS												
15611	L4.8WA19/8FCCTGC/D/E26	Clear	4.5	450	2700/3000/4000/5000	112.5	80	15,000	✓	40W	Damp	O
15613	L4.8WA19/8FCCTGF/D/E26	Frosted	4.5	450	2700/3000/4000/5000	112.5	80	15,000	✓	40W	Damp	P
15615	L8WA19/8FCCTGC/D/E26	Clear	8	800	2700/3000/4000/5000	100	80	15,000	✓	60W	Damp	O
15617	L8WA19/8FCCTGF/D/E26	Frosted	8	800	2700/3000/4000/5000	100	80	15,000	✓	60W	Damp	P
15619	L9.5WA19/8FCCTGC/D/E26	Clear	9.5	1100	2700/3000/4000/5000	115	80	15,000	✓	75W	Damp	O
15623	L9.5WA19/8FCCTGF/D/E26	Frosted	9.5	1100	2700/3000/4000/5000	115	80	15,000	✓	75W	Damp	P

PRODUCT DIMENSIONS

