



A15/A19 REPLACEMENT : E26 BASE

DESCRIPTION

LED A-Line Replacement Lamps directly replace incandescent A lamps at a fraction of the energy cost.

FEATURES

- Direct replacement for 40W, 60W, 75W, or 100W incandescent A-lamps
- 300° Omni beam angle is ideal for table lamps, wall sconces, and luminous globe fixtures
- 80% more efficient and 30x longer life than standard incandescent
- Shatter-resistant plastic housing for reduced risk of injury and breakage
- Compatible with a wide array of dimmers
- ANSI construction compliant
- Not for use with electronic timers, photocells, or motion/occupancy sensors

WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

APPLICATIONS

- Restaurants & Hospitality
- Retail
- Residential
- Accent/Display Lighting
- Healthcare



A15
E26



A19
E26



A19
GU24



A15 Colored
E26



PERFORMANCE	Power Consumption	5W	6W	8W	9W/9.5W	11W	15W
	Lumens	-	480	800	800	1,100	1,600
	Efficacy (LPW)	-	80	100	89	100	107
	CRI	80+					
	Beam	240°/300°					
	CCT	2700K/3000K/4000K/5000K					
	Life (L70)	10,000/15,000/25,000 hours					
ELECTRICAL	Power Factor	>0.7					
	Input Voltage	120V					
CONSTRUCTION	Operating Temperature	-4°F to 104°F (-20°C to 40°C)					
	Base	E26					
LISTINGS	Certification(s)	cULus Classified					
	Material Usage	RoHS Compliant; no mercury or lead					
	Environment	Suitable for damp locations; Enclosed fixture rated (select items)					

PERFORMANCE SUMMARY

A15 MEDIUM BASE (E26):

Order Code	Item #	Lumens	Watts	LPW	CCT	CRI	Beam	MOL	MOD	Life/Hours	Replaces Incan.
09976	LED5WA15/OMN/BLUE-G9	-	5W		Blue	-	300°	3.58"	1.89"	10K	-
09981	LED5WA15/OMN/RED-G8	-	5W		Red	-	300°	3.58"	1.89"	10K	-
09973	LED5WA15/OMN/YELLOW-G9*	-	5W		Yellow	-	300°	3.58"	1.89"	10K	-
10057	LED8WA15/OMN/827-DIM-G8*	800	8W		2700K	80+	240°	3.49"	1.97"	25K	60W A15
10058	LED8WA15/OMN/830-DIM-G8*	800	8W		3000K	80+	240°	3.49"	1.97"	25K	60W A15
10059	LED8WA15/OMN/840-DIM-G8*	800	8W		4000K	80+	240°	3.49"	1.97"	25K	60W A15

A19 MEDIUM BASE (E26):

Order Code	Item #	Lumens	Watts	LPW	CCT	CRI	Beam	MOL	MOD	Life/Hours	Replaces Incan.
09882	LED6WA19/OMN/827-DIM-G8*	480	6W		2700K	80+	300°	4.21"	2.36"	25K	40W A19
09887	LED6WA19/OMN/827-G8*	480	6W		2700K	80+	300°	4.33"	2.36"	25K	40W A19
09750	LED6WA19/OMN/830-G8*	480	6W		3000K	80+	300°	4.33"	2.36"	25K	40W A19
09751	LED6WA19/OMN/840-G8*	480	6W		4000K	80+	300°	4.33"	2.36"	25K	40W A19
09748	LED6WA19/OMN/830-DIM-G8*	480	6W		3000K	80+	300°	4.33"	2.36"	25K	40W A19
09749	LED6WA19/OMN/840-DIM-G8*	480	6W		4000K	80+	300°	4.33"	2.36"	25K	40W A19
09895	LED9WA19/OMN/827-DIM-G8*	800	9W		2700K	80+	300°	4.21"	2.36"	25K	60W A19
09896	LED9WA19/OMN/830-DIM-G8*	800	9W		3000K	80+	300°	4.21"	2.36"	25K	60W A19
09752	LED9WA19/OMN/840-DIM-G8*	800	9W		4000K	80+	300°	4.21"	2.36"	25K	60W A19
10060	LED9WA19/OMN/850-DIM-G8*	800	9W		5000K	80+	300°	4.21"	2.36"	25K	60W A19
09889	LED9.5WA19/OMN/827-G8*	800	9.5W		2700K	80+	300°	4.33"	2.36"	25K	60W A19
09753	LED9.5WA19/OMN/830-G8*	800	9.5W		3000K	80+	300°	4.33"	2.36"	25K	60W A19
09941	LED9.5WA19/OMN/840-G8*	800	9.5W		4000K	80+	300°	4.33"	2.36"	25K	60W A19
09885	LED11WA19/OMN/827-DIM-G8*	1,100	11W		2700K	80+	300°	4.33"	2.36"	25K	75W A19
09942	LED11WA19/OMN/830-DIM-G8*	1,100	11W		3000K	80+	300°	4.33"	2.36"	25K	75W A19
09943	LED11WA19/OMN/840-DIM-G8*	1,100	11W		4000K	80+	300°	4.33"	2.36"	25K	75W A19
10061	LED11WA19/OMN/850-DIM-G8*	1,100	11W		5000K	80+	300°	4.33"	2.36"	25K	75W A19
09886	LED15WA19/OMN/827-DIM-G8*	1,600	15W		2700K	80+	300°	4.33"	2.36"	25K	100W A19
09944	LED15WA19/OMN/830-DIM-G8*	1,600	15W		3000K	80+	300°	4.33"	2.36"	25K	100W A19
09945	LED15WA19/OMN/840-DIM-G8*	1,600	15W		4000K	80+	300°	4.33"	2.36"	25K	100W A19
09946	LED15WA19/OMN/850-DIM-G8*	1,600	15W		5000K	80+	300°	4.33"	2.36"	25K	100W A19

A19 GU24 BASE:

Order Code	Item #	Lumens	Watts	LPW	CCT	CRI	Beam	MOL	MOD	Life/Hours	Replaces Incan.
09974	LED9WA19/OMN/827-GU24-DIM-G8	800	9W		2700K	80+	300°	4.25"	2.36"	25K	60W A19
09975	LED9WA19/OMN/830-GU24-DIM-G8	800	9W		3000K	80+	300°	4.25"	2.36"	25K	60W A19
10108	LED9WA19/OMN/840-GU24-DIM-G8	800	9W		4000K	80+	300°	4.25"	2.36"	25K	60W A19
10122	LED11WA19/OMN/827-GU24-DIM-G8	1,100	11W		2700K	80+	300°	4.25"	2.36"	15K	75W A19
10014	LED11WA19/OMN/830-GU24-DIM-G8	1,100	11W		3000K	80+	300°	4.25"	2.36"	15K	75W A19
10100	LED11WA19/OMN/840-GU24-DIM-G8	1,100	11W		4000K	80+	300°	4.25"	2.36"	15K	75W A19
10125	LED15WA19/OMN/830-GU24-DIM-G8 †	1,600	15W		3000K	80+	300°	4.25"	2.36"	15K	75W A19

NOTE: Use order code when ordering. *Enclosed fixture rated. †Canada only.