



SLIM SURFACE DOWNLIGHT

- SLEEK LOOK
- INSTALLATION FLEXIBILITY
- HIGH CRI



KEY FEATURES :

	Three Sizes: 5.5", 7", 9"
	CCT Options: 5 color select (Field CCT) settings + fixed 3000K color temperature
	Triac or 0-10V Dimming <ul style="list-style-type: none">• 3000K - Triac Dimming, 120V• 5CCT - 0-10V Dimming, 120-277V
	Install Flexibility: Direct J-box or retrofit. Includes torsion springs for can installations
	80 or 90 CRI options. 90 CRI options for California/higher color rendering index needs
	EM Accessory for 7" model. EM Accessory for 7" model. When using EM accessory, it changes from wet location rating to damp location rating.
	Save Energy: ENERGY STAR® certified
	Airtight rated: CCT Select models are airtight rated
	Lifespan: 50,000 Hours
	Operating Temperature: -4F to 113F (-20C to 45C)



7" Slim Surface Downlight with emergency BBK



FIXTURES

Order Code	Name	Size	Voltage (VAC)	Wattage (W)	Lumens (lm)	CCT	CRI	RATED LIFE	Dimming
15143	SSD5.5-10W-830-120D-WH	5.5"	120V	10W	820 lm	3000K	80+	25,000	Triac
15145	SSD5.5-10W-8FCCT-UDIM-WH		120-277V			2700/3000/3500/4000/5000K	80+	50,000	0-10
15147	SSD7-12W-830-120DT-WH	7"	120V	12W	1000 lm	3000K	80+	25,000	Triac
15149	SSD7-12W-8FCCT-UDIM-WH		120-277V			2700/3000/3500/4000/5000K	80+	50,000	0-10
15151	SSD9-15W-830-120D-WH	9"	120V	15W	1230 lm	3000K	80+	25,000	Triac
15152	SSD9-15W-8FCCT-UDIM-WH		120-277V			2700/3000/3500/4000/5000K	80+	50,000	0-10
15153	SSD5.5-10W-9FCCT-UDIM-WH	5.5"	120-277V	10W	820 lm	2700/3000/3500/4000/5000K	90+	50,000	0-10
15154	SSD7-12W-9FCCT-UDIM-WH	7"		12W	1000 lm	2700/3000/3500/4000/5000K	90+	50,000	0-10

ACCESSORIES

Order Code	Name	Description
15155	SSD7EM	Slim Surface Downlight 7IN Battery Backup Accessory