



Jelly Jar Vapor Tight Fixture

HIGHLIGHTS

- One SKU for simplified stocking.
- Integrated photocell with manual on/off
- PowerSET feature allows for multiple lumen stops out of the box
- FieldCCeT feature provides multiple color temperature settings in one fixture
- Can be wall or ceiling mounted.

CERTIFICATIONS

- ETL listed for US & Canada
- RoHS Compliant
- FCC Compliant
- ICES-005 Compliant
- Wet Location
- IP65 Rated

PERFORMANCE

- PowerSET 3 Power settings (20/15/10W)
- FieldCCeT 3 CCT settings (3000/4000/5000K)
- CRI: >80
- Efficacy up to 80 LPW
- Lumen Maintenance 70% (L70): 50,000 Hours

ELECTRICAL

- Input voltage: 120-277V
- Surge protection: 2kV
- Power factor: >0.9
- THD: <20%

THERMAL

-22°F to 122°F (-30°C to 50°C) ambient operating temperature

CONSTRUCTION

- Die-cast aluminum construction
- Frosted glass lens
- Durable powder coated finish for corrosion resistance and maintence free housing
- Silicone seals to ensure vapor-proof performance
- Knock-outs are ½" trade size for conduit and access to various settings

WARRANTY

• 5 Year limited warranty available online. Contact your EiKO sales rep for additional details.

project name		type	
catalog nur	nber	voltage	
approved b	у	date	





Wall Mount

Ceiling Mount















APPLICATIONS

- Security lighting
- Entryways
- Perimeter lighting
- Industrial Parks
- Loading docks
- Walkways
- Landscape
- Garages
- Utility Rooms
- Restaurants/Lofts

AVAILABLE MODEL


ORDER	ORDER CODE	ITEM#	WATTS (W)	сст (к)	LUMENS (IM)	EFFICACY	CRI	V O LTA G E
	15593	JJ-PS20-8FCCT-U	20/15/10	3000/4000/5000	1600/1200/800	80	>80	120-277V

Fixture ships at the highest wattage setting, 4000K CCT, and photocell OFF.


POWER & CCT SELECT FEATURE INTEGRATED PHOTOCELL **POWER SET CCT SELECTABLE** 4K



PRODUCT DIMENSIONS









All KOs (5) are 1/2" Trade Size